STOCKHAM

Typical Bolted Bonnet Gate Features

Stockham gate valves offer the ultimate in dependable service for steam, air, gas, oil, oil vapor, and high pressure installations. All have straight-through ports to assure minimum turbulence, erosion, and resistance to flow. They are available in a wide variety of trims.

1. **Body:** Body is cast to provide liberal strength to meet operating conditions and to permit unobstructed flow. Turbulence, erosion and pressure drop are minimized.

Flanged End - Stockham cast steel gate valves are available in flanged end. All flanged end valves are designed to conform to ASME B16.5 and ASME B16.34 standards.

- Integral Yoke & Bonnet: Some designs incorporate a two-piece bonnet and yoke. All bonnet assemblies are cast and finished to the same exacting tolerances as the bodies for accurate alignment of stems and ease of sealing. Bonnet joint varies from flat face gasket-joint to ring-type bonnet joint, depending on class.
- 3. Seat Rings: Seat rings are seal welded to eliminate leak path behind rings and for long, trouble-free service. The surfaces are precisely ground to fit accurately 100 with the disc.
- 4. **Disc:** One piece flexible disc provides accurate alignment of mating seating surfaces so the valve can absorb piping strains without leakage. Also, it avoids any tendency to stick in the seated position.
- Stem: The tee-head disc-stem connection prevents lateral strain on the stem for smooth, easy operation. Accurately cut threads engage the yoke sleeve for positive control of disc position.
- 6. Yoke Sleeve
- 7. Handwheel Nut
- 8. Yoke Sleeve Retaining Nut
- 9. **Packing:** Packing contains corrosion inhibitor to avoid stem pitting. Stuffing box is deep, assuring long packing life.
- 10. **Gland:** Gland is a two-piece ball-type which exerts even pressure on the packing without binding the stem.
- 11. Gland Flange
- 12. Gland Eye Bolts: Eyebolts swing aside for ease in repacking the stuffing box.
- 13. Gland Eye Bolt Nuts
- 14. Bonnet Gasket
- 15. Bonnet Studs: Number is dependent on valve size and class.
- 16. Bonnet Nuts: Number is dependent on valve size and class.
- 17. Gland Eyebolt Pins
- 18. Bonnet Bushing
- 19. Handwheel: Stockham gate valves can also be supplied with gear or motor operators.
- 20. **Hydraulic Grease Fitting:** Hydraulic grease fitting provides for lubrication of yoke sleeve bearing surfaces (not shown).

1B

NOTE: Stockham recommends the use of gear assistance for certain multi-turn valves for optimal functional performance in larger sizes and high flowrate applications. Please refer to the note on specific product pages.