

Self-Laminating Vinyl Wire and Cable Labels (B-427)

Labels feature a clear, non-printable area that wraps around print-on area to protect text. Vinyl material offers superior resistance to handling, solvents, oil, grease, dirt and water. Temp. range -40° F to 158° F (-40° C to 70° C), UL recognized.




Figure 32




Figure 42b



Fits Printers	Figure	Catalog#	Color	Approx. Wire Gauge	Max Wire Dia. Inch (mm)	Label Width A Inch (mm)	Label Height B Inch (mm)	Print-On Height C Inch (mm)	Labels Per Roll	Sized To Fit	Ribbon in Cartridge
BMP41, 51, 53	Fig. 32	M-11-427	BK on WT	16 to 10	0.160 (4.1)	0.500 (12.7)	0.750 (19.1)	0.375 (9.5)	360	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-136-427	BK on WT	16 to 10	0.160 (4.1)	1.000 (25.4)	0.750 (19.1)	0.375 (9.5)	340	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 42b	MC-750-427	BK on WT	16 to 10	0.270 (6.7)	25 ft. (7.6 m)	0.750 (19.1)	0.375 (9.5)	1 roll (cont.)	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-47-427	BK on WT	12 to 10	0.210 (5.3)	1.000 (25.4)	0.500 (12.7)	0.375 (9.5)	360	2 pair Fiber/Coaxial, Single/Multi-Mode	R4300
BMP41, 51, 53	Fig. 32	M-48-427	BK on WT	12 to 10	0.210 (5.3)	0.750 (19.1)	1.000 (25.4)	0.375 (9.5)	200	CAT-6, 4 pair UTP Copper, Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-49-427	BK on WT	12 to 10	0.210 (5.3)	1.000 (25.4)	1.000 (25.4)	0.375 (9.5)	260	2 pair Fiber/Coaxial, Single/Multi-Mode	R4300
BMP41, 51, 53	Fig. 32	M-102-427	BK on WT	10 to 4	0.270 (6.7)	0.500 (12.7)	1.250 (31.7)	0.375 (9.5)	200	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-143-427	BK on WT	10 to 4	0.270 (6.7)	1.000 (25.4)	1.250 (31.7)	0.500 (12.7)	200	CAT-6, 4 pair UTP Copper, Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-89-427	BK on WT	10 to 4	0.320 (8.1)	0.500 (12.7)	1.500 (38.1)	0.500 (12.7)	180	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-90-427	BK on WT	10 to 4	0.320 (8.1)	0.750 (19.1)	1.500 (38.1)	0.500 (12.7)	180	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-91-427	BK on WT	10 to 4	0.320 (8.1)	1.000 (25.4)	1.500 (38.1)	0.500 (12.7)	180	CAT-6, 4 pair UTP Copper, Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-51-427	BK on WT	3 to 2/0	0.530 (13.5)	1.000 (25.4)	2.500 (63.5)	0.750 (19.1)	110	25 pair Copper, 4-12 pair Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-53-427	BK on WT	3/0 to 400 kcmil	0.850 (21.6)	1.000 (25.4)	4.000 (101.6)	1.000 (25.4)	70	50 pair Copper, 24 pair Fiber, Backbone	R4300
BMP41, 51, 53	Fig. 32	M-91-427-YL	BK on YL	10 to 4	0.320 (8.1)	1.000 (25.4)	1.500 (38.1)	0.500 (12.7)	180	CAT-6, 4 pair UTP Copper, Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-51-427-YL	BK on YL	3 to 2/0	0.530 (13.5)	1.000 (25.4)	2.500 (63.5)	0.750 (19.1)	110	25 pair Copper, 4-12 pair Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-53-427-YL	BK on YL	3/0 to 400 kcmil	0.850 (21.6)	1.000 (25.4)	4.000 (101.6)	1.000 (25.4)	70	50 pair Copper, 24 pair Fiber, Backbone	R4300

PermaSleeve[®] PS Polyolefin Wire Markers (B-342)

Military / industrial grade sleeves offer the ultimate in marker durability, permanence and aesthetic appearance. 3:1 heat-shrinkable markers fit snugly around wires, are fade-resistant and flame-retardant. Temp range: -67° F to 275° F (-55° C to 130° C). RoHS compliant and UL recognized.

Meets specifications:

- SSAE-AS-23053/5
- SAE-AS-81531

Tested per:

- ASTM E162
- ASTM E662
- MIL-STD-202




Figure 44




Figure 58



Fits Printers	Figure	Catalog #	B#	Color	Approx. Wire Gauge	Wire Diameter Range Inch (mm)	Supplied Diameter B Inch (mm)	Supplied Width A Inch (mm)	Sleeves Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 44	* M-125-075-342	B-342	BK on WT	22 to 16	0.046 - 0.110 (1.2 - 2.8)	0.235 (5.9)	0.750 (19.1)	80	R4300
BMP41, 51, 53	Fig. 58	* MC-125-342	B-342	BK on WT	22 to 16	0.046 - 0.110 (1.2 - 2.8)	0.235 (5.9)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 44	* M-187-075-342	B-342	BK on WT	20 to 10	0.062 - 0.150 (1.6 - 3.8)	0.335 (8.5)	0.750 (19.1)	80	R4300
BMP41, 51, 53	Fig. 58	* MC-187-342	B-342	BK on WT	20 to 10	0.062 - 0.150 (1.6 - 3.8)	0.335 (8.5)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 44	* M-250-075-342	B-342	BK on WT	16 to 8	0.094 - 0.215 (2.4 - 5.5)	0.439 (11.1)	0.750 (19.1)	80	R4300
BMP41, 51, 53	Fig. 58	* MC-250-342	B-342	BK on WT	16 to 8	0.094 - 0.215 (2.4 - 5.5)	0.439 (11.1)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 44	* M-375-075-342	B-342	BK on WT	12 to 4	0.125 - 0.320 (3.2 - 8.1)	0.645 (16.4)	0.750 (19.1)	80	R4300
BMP41, 51, 53	Fig. 58	* MC1-375-342	B-342	BK on WT	12 to 4	0.125 - 0.320 (3.2 - 8.1)	0.645 (16.4)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-125-342-YL	B-342	BK on YL	22 to 16	0.046 - 0.110 (1.2 - 2.8)	0.235 (5.9)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-187-342-YL	B-342	BK on YL	20 to 10	0.062 - 0.150 (1.6 - 3.8)	0.335 (8.5)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-250-342-YL	B-342	BK on YL	16 to 8	0.094 - 0.215 (2.4 - 5.5)	0.439 (11.1)	7 ft. (2.1 m)	1 roll (cont.)	R4300

* **WARNING:** Cancer www.P65Warnings.ca.gov

Nylon Cloth Cable Flags (B-499)

Pre-formatted with two printable areas, allowing flag to be easily folded around wire to create a two-sided, printed flag. Nylon Cloth with permanent adhesive is pliable for rough or smooth surfaces. Temp. range: -94° F to 194° F (-70° C to 90° C). UL recognized.





Figure 63



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Non-Print Area Inch (mm)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 63	M-141-499	B-499	Nylon Cloth	BK on WT	1.000 (25.4)	1.000 (25.4)	0.250 (6.3)	90	R4300

Repositionable Adhesive Vinyl Cloth Wire and Cable Labels (B-498)

Printer automatically repeats your text to fill the label for maximum readability. The adhesive and cloth backing offers excellent holding power, yet allow for clean removal and repositioning if necessary. Temp. range -40° F to 175° F (-40° C to 70° C). UL recognized.




Fits Printers	Figure	Catalog #	B#	Material	Color	Approx. Wire Gauge	Max. Wire Dia. Inch (mm)	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 2	M-7-498	B-498	Vinyl	BK on WT	22 to 16	0.110 (2.8)	0.500 (12.7)	0.500 (12.7)	240	R6200
BMP41, 51, 53	Fig. 2	M-11-498	B-498	Vinyl	BK on WT	16 to 10	0.160 (4.1)	0.750 (19.1)	0.500 (12.7)	220	R6200
BMP41, 51, 53	Fig. 2	M-48-498	B-498	Vinyl	BK on WT	12 to 10	0.210 (5.3)	1.000 (25.4)	0.750 (19.1)	180	R6200
BMP41, 51, 53	Fig. 2	M-49-498	B-498	Vinyl	BK on WT	12 to 10	0.210 (5.3)	1.000 (25.4)	1.000 (25.4)	160	R6200
BMP41, 51, 53	Fig. 2	M-131-498	B-498	Vinyl	BK on WT	10 to 4	0.270 (6.7)	1.000 (25.4)	0.500 (12.7)	180	R6200
BMP41, 51, 53	Fig. 2	M-91-498	B-498	Vinyl	BK on WT	10 to 4	0.270 (6.7)	1.500 (38.1)	1.000 (25.4)	120	R6200

Patch Panel, Punch Block, Desi Strip and Faceplate Labels (B-412 and B-422)

Create a fully formatted serialized punch block label to fit your equipment or label your ports, jacks and outlets with adhesive labels or slide-in strips.



- **B-412 Polypropylene Tags:** Non-adhesive slide-in strips
- **B-422 Polyester Material:** Permanent adhesive, good for powder-coated/textured surfaces. Temp. range: -40° F to 212° F (-40° C to 100° C). UL recognized.



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-412 Non-Adhesive Polypropylene Tags									
BMP41, 51, 53	Fig. 33c	MC-375-412	B-412	Polypropylene	BK on WT	0.375 (9.5)	20 ft. (6.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33c	MC-475-412	B-412	Polypropylene	BK on WT	0.475 (12.1)	20 ft. (6.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33c	MC-625-412	B-412	Polypropylene	BK on WT	0.625 (15.8)	20 ft. (6.1 m)	1 roll (cont.)	R4300
B-422 Polyester Material									
BMP41, 51, 53	Fig. 33c	MC-375-422	B-422	Polyester	BK on WT	0.375 (9.5)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33c	MC-475-422	B-422	Polyester	BK on WT	0.475 (12.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-7-422	B-422	Polyester	BK on WT	0.500 (12.7)	0.500 (12.7)	280	R6000
BMP41, 51, 53	Fig. 2	M-89-422	B-422	Polyester	BK on WT	0.500 (12.7)	1.500 (38.1)	180	R6000
BMP41, 51, 53	Fig. 2	M-90-422	B-422	Polyester	BK on WT	0.750 (19.1)	1.500 (38.1)	180	R6000
BMP41, 51, 53	Fig. 2	M-47-422	B-422	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480	R6000

Terminal Block Repositionable Adhesive Strips (B-498)

When using terminal block mode, printer can serialize and pre-space to your special thin widths to fit terminal blocks. The adhesive and cloth backing offers excellent holding power, yet allow for clean removal and repositioning if necessary. Temp. range -40° F to 175° F (-40° C to 70° C). UL recognized.



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Feet (m)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 33c	MC-240-498	B-498	Vinyl	BK on WT	0.240 (6.1)	16 (4.9)	1 roll (cont.)	R6200
BMP41, 51, 53	Fig. 33c	MC-318-498	B-498	Vinyl	BK on WT	0.318 (8.1)	16 (4.9)	1 roll (cont.)	R6200
BMP41, 51, 53	Fig. 33c	MC-375-498	B-498	Vinyl	BK on WT	0.375 (9.5)	20 (6.1)	1 roll (cont.)	R6200