

# NEER™ Zinc Gland Compression Connectors and Couplings

For EMT.

NEC/CEC:  
Listed for Ordinary Locations

NEC/CEC:  
Listed for Ordinary Locations

## TC-600: Couplings

### Application

- To join lengths of steel EMT for concretetight, dry or damp location applications.

### Features

- Concretetight.
- Raintight (wet locations) Canada.

### Material/Finish

- Zinc diecast

### NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14895
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 208044
- NEMA: FB-1



TC-611

Trade Size (Inches)	Dimensions in Millimeters (Inches)			Catalog Number
	Body Length	Maximum Diameter		
1/2	43.2 (1.70)	24.9 (0.98)		TC-611
3/4	45.2 (1.78)	30.7 (1.21)		TC-612
1	46.2 (1.82)	38.6 (1.52)		TC-613
1-1/4	53.8 (2.12)	46.5 (1.83)		TC-614
1-1/2	59.7 (2.35)	54.1 (2.13)		TC-615
2	62.7 (2.47)	64.8 (2.55)		TC-616
2 - 1/2 <sup>Ⓢ</sup>	83.3 (3.28)	83.8 (3.30)		TC-617 <sup>Ⓢ</sup>
3 <sup>Ⓢ</sup>	85.1 (3.35)	100.1 (3.94)		TC-618 <sup>Ⓢ</sup>
3 - 1/2 <sup>Ⓢ</sup>	89.9 (3.54)	126.2 (4.97)		TC-619 <sup>Ⓢ</sup>
4	89.9 (3.54)	126.2 (4.97)		TC-620 <sup>Ⓢ</sup>

<sup>Ⓢ</sup> For EMT and threadless rigid metal conduit and IMC.

## TC-600: Connectors

### Application

- To secure and terminate steel EMT to knockouts in concretetight box, dry or damp location applications.

### Features

- Male hub threads — NPS.
- Concretetight.
- Available with insulated throat.
- Furnished with locknut.

### Material/Finish

- Zinc diecast

### NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14895
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 208044
- NEMA: FB-1



TC-601

Trade Size (Inches)	Dimensions in Millimeters (Inches)				Catalog Number	Insulated Throat Catalog Number
	Body Length	Maximum Diameter	Thread Length			
1/2	32.0 (1.26)	10.2 (0.40)	24.9 (0.98)		TC-601	TCI-601
3/4	32.8 (1.29)	10.2 (0.40)	30.7 (1.21)		TC-602	TCI-602
1	36.6 (1.44)	10.9 (0.43)	38.6 (1.52)		TC-603	TCI-603
1-1/4	44.2 (1.74)	16.0 (0.63)	46.5 (1.83)		TC-604	TCI-604
1-1/2	47.2 (1.86)	16.5 (0.65)	54.1 (2.13)		TC-605	TCI-605
2	54.6 (2.15)	18.5 (0.73)	64.8 (2.55)		TC-606	TCI-606
2 - 1/2 <sup>Ⓢ</sup>	66.5 (2.62)	23.1 (0.91)	83.8 (3.30)		TC-607 <sup>Ⓢ</sup>	TCI-607 <sup>Ⓢ</sup>
3 <sup>Ⓢ</sup>	68.3 (2.69)	24.4 (0.96)	100.1 (3.94)		TC-608 <sup>Ⓢ</sup>	TCI-608 <sup>Ⓢ</sup>
3 - 1/2 <sup>Ⓢ</sup>	72.1 (2.84)	24.4 (0.96)	126.2 (4.97)		TC-609 <sup>Ⓢ</sup>	TCI-609 <sup>Ⓢ</sup>
4	72.1 (2.84)	24.4 (0.96)	126.2 (4.97)		TC-610 <sup>Ⓢ</sup>	TCI-610 <sup>Ⓢ</sup>