

Reducing Washers

NEC/CEC:
Listed for Ordinary Locations

Applications

- To reduce a knockout or sliphole in a sheet metal enclosure to a smaller trade size.

Material

- Steel

NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14817
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E14817
- NEMA: FB-1

Trade Size (Inches)	Dimensions in Millimeters (Inches)			Weight per 100 kg (lb)	Catalog Number
	A	B	C		
Reducing Washers — Steel					
3/4 to 1/2	34.0 (1.34)	22.4 (0.88)	—	0.54 (1.20)	RW75-50
1 to 1/2	42.9 (1.69)	22.4 (0.88)	—	1.09 (2.40)	RW100-50
1 to 3/4	42.9 (1.69)	28.2 (1.11)	—	0.91 (2.00)	RW100-75
1-1/4 to 1/2	51.6 (2.03)	22.4 (0.88)	—	2.27 (5.00)	RW125-50
1-1/4 to 3/4	51.6 (2.03)	28.2 (1.11)	—	1.99 (4.40)	RW125-75
1-1/4 to 1	51.6 (2.03)	35.1 (1.38)	—	1.36 (3.00)	RW125-100
1-1/2 to 1/2	57.9 (2.28)	22.4 (0.88)	—	2.99 (6.60)	RW150-50
1-1/2 to 3/4	57.9 (2.28)	28.2 (1.11)	—	2.72 (6.00)	RW150-75
1-1/2 to 1	57.9 (2.28)	35.1 (1.38)	—	2.27 (5.00)	RW150-100
1-1/2 to 1-1/4	57.9 (2.28)	43.9 (1.73)	—	1.81 (4.00)	RW150-125
2 to 1/2	69.9 (2.75)	22.4 (0.88)	—	4.54 (10.00)	RW200-50
2 to 3/4	69.9 (2.75)	28.2 (1.11)	—	3.63 (8.00)	RW200-75
2 to 1	69.9 (2.75)	35.1 (1.38)	—	3.63 (8.00)	RW200-100
2 to 1-1/4	69.9 (2.75)	43.9 (1.73)	—	3.18 (7.00)	RW200-125
2 to 1-1/2	69.9 (2.75)	50.3 (1.98)	—	2.27 (5.00)	RW200-150

