Product data sheet Characteristics

2510FG1

Manual motor starter, fractional horsepower, 1 P, 16 amp, toggle operated, no pilot light, NEMA 1 enclosure

Product availability: Stock - Normally stocked in distribution facility



Price*: 90.37 USD



Main

Product	Single Unit Manual Starter	-
Туре	F	,
Overload Relay Type	Melting alloy	

Complementary

		-
Line Rated Current	16 A	
Cable entry	0.5" and 0.75" knock-outs (top and bottom)	
Horsepower Rating	1 hp at 115 V AC 1 hp at 230 V AC 1 hp at 277 V AC	,
System Voltage	277 V AC	
Number of Poles	1P	
Control Unit	Toggle switch	
Phase	1 phase	
Pilot Light	No indicator	
Reset	Manual	
Motor starter type	Non reversing	7
Electrical connection	Screw clamp terminals	7
Wire Gauge	AWG 14AWG 12 (copper)	
Height	4.25 in	? ?
Width	2.44 in	
Depth	2.75 in	

Environment

Product certifications CSA LR25490 class 3211 05

UL listed file E42243 CCN NLRV

NEMA Enclosure Rating	NEMA 1 plastic standard size
-----------------------	------------------------------

Ordering and shipping details

Category	21101 - 2510,2511,2512 F
Discount Schedule	CP1
GTIN	00785901553939
Nbr. of units in pkg.	1
Package weight(Lbs)	1.46
Returnability	Υ
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant	
	Will not be compliant	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1 Lead and lead compounds, which is known to the State of California to cause of defects or other reproductive harm.		
More information	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty period	18 months