Product data sheet Characteristics

2510FO1

Manual motor starter, fractional horsepower, 1 P, 16 amp, toggle operated, no pilot light, open

Product availability : Stock - Normally stocked in distribution facility



Price* : 74.56 USD



Main

Product	Single Unit Manual Starter
Туре	F
Overload Relay Type	Melting alloy

Complementary

011		
Maia		
Main Product	Single Unit Manual Starter	
	F	
Type		
Overload Relay Type	Melting alloy	
Complementary		
Line Rated Current	16 A	
Cable entry	Without	
Horsepower Rating	1 hp at 115 V AC	
	1 hp at 230 V AC 1 hp at 277 V AC	
System Voltage	277 V AC	
Number of Poles	1P	
Control Unit	Toggle switch	·
Phase	1 phase	
Pilot Light	No indicator	
Reset	Manual .	
Motor starter type	Non reversing	
Electrical connection	Screw clamp terminals	
Wire Gauge	AWG 14AWG 12 (copper)	
Height	4.13 in	
Width	1.69 in	
Depth	2.22 in	
Environment		
Product certifications	CSA LR25490 class 3211 05 UL recognized E42243 CCN NLRV2	
W14 0040		

Environment

Product certifications	CSA LR25490 class 3211 05
	UL recognized E42243 CCN NLRV2

Life Is On Schneider

Ordering and shipping details

erdering and empping det	
Category	21101 - 2510,2511,2512 F
Discount Schedule	CP1
GTIN	00785901554134
Nbr. of units in pkg.	1
Package weight(Lbs)	0.320000000000001
Returnability	Y
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant	
	Will not be compliant	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty period

18 months