# Product data sheet Characteristics

## 8536SBO2V02H30S

Type S nonreversing magnetic starter, NEMA Size 0, 3 P, 110/120 VAC 50/60 Hz coil, Motor Logic overload, open

Product availability: Stock - Normally stocked in distribution facility



Price\*: 578.00 USD



#### Main

Product or component type	Starter
Туре	S
Control Circuit Type	Separate control circuit

#### Complementary

Complementary		<u>.</u>
Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Motor starter type	Non reversing	:
Line Rated Current	18 A	
Number of Poles	3P	
Phase	3 phases	
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	:
System Voltage	600 V AC	
Control Units	No control units	
Thermal overload type	Solid state Motor Logic class 10/20	
Electrical connection	Screw clamp terminals	
NEMA size	0	
Height	6.77 in (172 mm)	
Depth	4.21 in (107 mm)	
Width	3.5 in (89 mm)	

#### Environment

Enclosure Type	Not rated (open device)
Product certifications	CSA UL listed NEMA

#### Ordering and shipping details

3 - 1 - 3 - 1	
Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901807315
Nbr. of units in pkg.	1
Package weight(Lbs)	3.96
Returnability	Υ
Country of origin	MX
· -	

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1545 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

#### Contractual warranty

Warranty period	18 months