Product data sheet Characteristics

9070T250D1 TRANSFORMER CONTROL 250VA 240/480V-120V

Product availability: Stock - Normally stocked in distribution facility





Price*: 239.00 USD



Main

IVICIII		
Product or component type	Industrial Control Transformer 250 VA	
Power Rating		
Primary Voltage	240 x 480 V	
	230 x 460 V	
	220 x 440 V	<u>.</u>
Secondary Voltage	120 V	
	115 V	<u> </u>
	110 V	
Туре	Т	
		<u>.</u> .

Complementary

Phase	1 phase 250 VA per UL 250 VA per CSA 250 VA per NOM 160 VA per CE		
Power Rating			
Primary to Secondary Voltage	220 x 440 V : 110 V 230 x 460 V : 115 V 240 x 480 V : 120 V		
Temperature rise	80 °C		
Electrical connection	Screw clamp terminals		
Height	3.2 in		
Width	3.75 in		
Depth	5.3 in		
Material	5.3 in Copper winding		
Fingersafe Cover Compatibility	FSC2		

Environment

Product certifications	CE UL listed file E61239 CSA file LR37055 guide 184-N-90	
Enclosure Type	Not rated (open device)	
Insulation temperature	266 °F (130 °C)	

Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA		
Discount Schedule	CP8		
GTIN	00785901904670		
Nbr. of units in pkg.	1		
Package weight(Lbs)	7.9199999999999		
Returnability	Υ		
Country of origin	MX		

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

Contractual warranty

	•		
Warranty period		10 years	