## Product data sheet Characteristics

# **D222N** SWITCH FUSIBLE GD 240V 60A 2P NEMA1

Product availability: Stock - Normally stocked in distribution facility





Price\*: 206.00 USD



#### Main

| Wichiii                      |  |
|------------------------------|--|
| Product                      | Single Throw Safety Switch                 |
| Line Rated Current           | 60 A                                       |
| Certifications               | UL listed                                  |
| Enclosure Rating             | NEMA 1                                     |
| Disconnect Type              | Fusible disconnect                         |
| Factory Installed Neutral    | Neutral (factory installed)                |
| Short Circuit Current Rating | 100 kA maximum depending on fuse H, K or R |
| Mounting Type                | Surface                                    |
| Number of Poles              | 2  |
| Electrical Connection        | Lugs                                       |
| Duty Rating                  | General duty                               |
|                              |  |

#### Ordering and shipping details

| Category              | 00006 - D & DU SW, NEMA1, 30-200A |  |
|-----------------------|-----------------------------------|--|
| Discount Schedule     | DE1A                              |  |
| GTIN                  | 00785901460626                    |  |
| Nbr. of units in pkg. | 1                                 |  |
| Package weight(Lbs)   | 7.770000000000005                 |  |
| Returnability         | Υ                                 |  |
| Country of origin     | US                                |  |

### Offer Sustainability

| Main                          |   |  |
|-------------------------------|---|--|
| Product                       | Single Throw Safety Switch  |  |
| Line Rated Current            | 60 A  |  |
| Certifications                | UL listed   |  |
| Enclosure Rating              | NEMA 1  |  |
| Disconnect Type               | Fusible disconnect  |  |
| Factory Installed Neutral     | Neutral (factory installed)   |  |
| Short Circuit Current Rating  | 100 kA maximum depending on fuse H, K or R                            |  |
| Mounting Type                 | Surface   |  |
| Number of Poles               | 2   |  |
| Electrical Connection         | Lugs  |  |
| Duty Rating                   | General duty  |  |
| Ordering and shipping details |   |  |
| Category                      | 00006 - D & DU SW, NEMA1, 30-200A                                     |  |
| Discount Schedule             | DE1A  |  |
| GTIN                          | 00785901460626  |  |
| Nbr. of units in pkg.         | 1   |  |
| Package weight(Lbs)           | 7.770000000000005   |  |
| Returnability                 | Υ   |  |
| Country of origin             | US  |  |
|                               |   |  |
| Offer Sustainability          |   |  |
| Sustainable offer status      | Green Premium product   |  |
| RoHS (date code: YYWW)        | Compliant - since 1313 - Schneider Electric declaration of conformity |  |
|                               | Schneider Electric declaration of conformity                          |  |
| REACh                         | Reference not containing SVHC above the threshold                     |  |
| May 24, 2040                  |   |  |

#### Reference not containing SVHC above the threshold

| Product environmental profile    | Available  |
|----------------------------------|--|
| Product end of life instructions | Need no specific recycling operations  |
| California proposition 65        | WARNING: This product can expose you to chemicals including:   |
| Substance 1                      | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| More information                 | For more information go to www.p65warnings.ca.gov  |

### Contractual warranty

| Warranty period | 18 months |
|-----------------|-----------|
| Warranty period |           |
|                 |           |