Product data sheet Characteristics

8536SBG2V02S

Type S nonreversing magnetic starter, NEMA Size 0, 3 P, 110/120 VAC 50/60 Hz coil, melting alloy overload, NEMA 1

Product availability: Stock - Normally stocked in distribution facility



Price*: 518.00 USD



Main

Product or component type	Starter	
Туре	S	
Control Circuit Type	Separate control circuit	

Complementary

Complementary		
Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Motor starter type	Non reversing	
Line Rated Current	18 A	
Number of Poles	3P	
Phase	3 phases	
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	:
System Voltage	600 V AC	
Control Units	No control units	
Thermal overload type	Melting alloy 3 Thermal Units	
Electrical connection	Screw clamp terminals	
NEMA size	0	
Height	10 in (254 mm)	
Depth	5.55 in (141 mm)	<u> </u>
Width	5.98 in (152 mm)	

Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	CSA NEMA UL listed

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901864608
Nbr. of units in pkg.	1
Package weight(Lbs)	7.2599999999998
Returnability	Υ
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant	
	Will not be compliant	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty period	18 months