Product data sheet Characteristics

8536SBG2V03

Non-Reversing Starter Size 0, 3-Pole, Melting Alloy Overload, NEMA 1

Product availability: Stock - Normally stocked in distribution facility



Price*: 518.00 USD



Main

| Product or component type | Starter |
|---------------------------|------------------------|
| Туре | S |
| Control Circuit Type | Common control circuit |

Complementary

| Complementary | | |
|-------------------------|--|---------------------------------------|
| Control Circuit Voltage | 220 V AC 50 Hz 240 V AC 60 Hz | - 191 141 141 141 |
| Motor starter type | Non reversing | |
| Line Rated Current | 18 A | |
| Number of Poles | 3P | , , , , , , , , , , , , , , , , , , , |
| Phase | 3 phases | 9 |
| Horsepower Rating | 3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC | od det se de |
| System Voltage | 600 V AC | |
| Control Units | No control units | |
| Thermal overload type | Melting alloy 3 Thermal Units | ū a |
| Electrical connection | Screw clamp terminals | |
| NEMA size | 0 | ir Strain |
| Height | 10 in (254 mm) | <u>.</u> |
| Depth | 5.55 in (141 mm) | . <u>u</u> |
| Width | 5.98 in (152 mm) | ter |
| | | 5 |

Environment

| LIIVIIC | minorit | | |
|---------|----------------|----------------------------|-------|
| Enclosi | иге Туре | NEMA 1 painted sheet steel | mer. |
| Produc | certifications | CSA | ISCIA |

Ordering and shipping details

| Category | 21191 - 8502,36 SA,SB(NOT S*R,T,W) |
|-----------------------|------------------------------------|
| Discount Schedule | CP1 |
| GTIN | 00785901869108 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 7.29 |
| Returnability | Υ |
| Country of origin | MX |

Offer Sustainability

| RoHS (date code: YYWW) | Will not be compliant |
|---------------------------|--|
| | Will not be compliant |
| California proposition 65 | WARNING: This product can expose you to chemicals including: |
| Substance 1 | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| More information | For more information go to www.p65warnings.ca.gov |

Contractual warranty

| Warranty period 18 months |
|---------------------------|
|---------------------------|