# Product data sheet Characteristics

# 2510MBG2

Manual starter, integral horsepower, NEMA size M0, 3 P, push button control, no pilot light, 600 VAC, NEMA 1 enclosure

Product availability: Stock - Normally stocked in distribution facility



Price\*: 323.40 USD



## Main

Product	Manual Starter	· ·
Туре	M	
NEMA Size	M-0	

### Complementary

Control Unit	Push-button	
Pilot Light	No indicator	i
Horsepower Rating	3 hp at 200230 V AC 3 phases 5 hp at 380575 V AC 3 phases	— for dete
System Voltage	600 V AC	— Sesin
Number of Poles	3P	
Starter Type	Non reversing	
Electrical Connection	Pressure wire clamp	bue
Overload Relay Type	Melting alloy	fg
Number of Thermal Units Required	3	— pstiti
Wire Gauge	AWG 14AWG 8 (copper)	
Auxiliary Contacts	Without	Se pe
Height	8.63 in	
Width	5 in	<u>.</u>
Depth	4.13 in	<u>v</u>
		<u></u>

#### **Environment**

Environment		7
Certifications	UL listed file E42243 CCN NLRV CSA LR60905 class 3211 05	er: This
NEMA Enclosure Rating	NEMA 1 painted sheet steel	

# Ordering and shipping details

Category	21103 - 2510,2511,2512 M,T
Discount Schedule	CP1
GTIN	00785901792536
Nbr. of units in pkg.	1
Package weight(Lbs)	4.150000000000004
Returnability	Υ
Country of origin	MX

## Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant	
	Will not be compliant	
California proposition 65 WARNING: This product can expose you to chemicals including:		
Substance 1 Lead and lead compounds, which is known to the State of California to cat defects or other reproductive harm.		
More information	For more information go to www.p65warnings.ca.gov	

## Contractual warranty

Warranty period	18 months	