



Price* : 1,195.20 USD



Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip Unit Type	Thermal-magnetic
Rating Code	A

Complementary

Line Rated Current	80 A
Number of Poles	3P
Interrupt Rating	18 kA at 480 V AC 25 kA at 240 V AC 10 kA at 250 V DC
System Voltage	250 V DC 480 V AC
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
Wire Gauge	AWG 14...AWG 4 (copper) 1 cable(s) AWG 12...AWG 4 (aluminium) 1 cable(s)
Terminal Type	AL50FA
Magnetic hold current	800 A
Magnetic tripping current	1450 A
Phase connection	ABC
Height	6.4 in
Width	4.5 in
Depth	4.13 in

Environment

Product certifications	CSA
------------------------	-----

UL listed

Ordering and shipping details

Category	01005 - FA 480V BREAKER & SWITCH
Discount Schedule	DE2
GTIN	00785901342502
Nbr. of units in pkg.	1
Package weight(Lbs)	6.169999999999999
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including:
----- Substance 1	DINP, which is known to the State of California to cause cancer, and
----- Substance 2	DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.
----- More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

FA34080 is replaced by:



I-Line BDA36080

PowerPact - circuit breaker - 80A 3P AC 18kA at 600Y/347V (UL) - I-Line

Qty 1

Reason for Substitution: End of life | Substitution date: 15 December 2018 | (Ref #) is replaced by (New Ref #)