

#### Features:

- · premium brass and zinc construction for maximum strength and durability
- patented impact resistant clamp design
- · non-corroding high grade 410 stainless steel screws will not strip when tightened
- leakproof, reusable
- for use with rubber or plastic hose
- fits all %" and 34" hose

## **Female Hose Fittings**

Part #	Optional Qty		
M5834F	48		



## **Male Hose Fittings**

Part #	Optional Qty		
M5834M	48		



### **Menders**

Part #	Optional Qty		
М5834НМ	48		



# **Male GHT Adapters**

# Male Hose x Male Hose x Female Pipe

Male GH x Male GH x	Lead Free Brass	
Female NPT	Part #	
3/4" X 3/4" X 1/2"	5091212CLF	



### Male GHT x Male NPTF







brass

lead free brass

303 stainless

Male GHT	Male NPTF	Bi Previous Part #	rass Part #	Lead Free Brass³ Part #	Male Thread	303 S Previous Part #	tainless Part #	Pkg Qty
3/4"	3/8"	BA73	5081206C 1					25
3/4"	1/2"	BA74	5081208C 1	5081208CLF	NPT	RA74	5081208SS	25
3/4"	3/4"		5081212C 1		NPT	RA776	5081212SS	25
3/4"	3⁄4" X 1⁄2"	BA776	5141212C 1,2	5141212CLF <sup>2</sup>	NPT		5141212SS <sup>2</sup>	25
3/4"	1"	BA78	5081216C 1					10

<sup>&</sup>lt;sup>1</sup> extended male GHT, deeper thread

 $<sup>^{2}~\</sup>mbox{has}~\mbox{1/2}"$  female NPT on ID of  $\mbox{3/4}"$  male NPT side

<sup>&</sup>lt;sup>3</sup> Lead free brass <=0.25% lead; Alloy CA2745; Alloy C46400